

# LIGHTINGRETROFIT

## Induction ceiling light

## LRF-XD003A-150W

### Technical Data

Power - 150W

Voltage - 220vac      Current - 0.68A

Power Factor - > 0.95

Operating Frequency - 230KHz (no flicker)

Operating Temperature range - -25degC to +50degC

Maximum Operating Temperature - +85degC

Ingress Protection - IP54

Certification - CE, CCC, RoHS, FCC approvals and IEC55015, IEC61347 compliance reports.

Colour Temperature - 3000-6500 Kelvin (5000K is stock item, other colours to order)

Colour Render Index - >85Ra

Total Lumens \* - 12,300      Lumens per Watt \* - 82

P/S ratio - 1.96      Total Pupil Lumens \* - 24,110

Lumen Maintenance - @ 2,000hrs => 95%, @16,000hrs=> 90%, @60,000hrs => 80%


Dimensions - Powder coated housing 58cm square by 25cm high, 12.6kg weight

Reflector Cover - UV proof polycarbonate diffuser

Switching - Instant switching

Life span / Warranty - 80,000 hours average / 2 year lamp and ballast parts warranty

\* Subject to 3% variation up or down per fitting



Baytrade Nominees Pty Ltd  
ABN 77 082 123 117  
[lightingretrofit.aus@gmail.com](mailto:lightingretrofit.aus@gmail.com)

