

LIGHTINGRETROFIT

Induction Lamp & Ballast Kit LRF-UVL150 to 300

Technical Data

Power - 150W to 300W

Current - 0.68A (150W) to 1.36A(300W) at nominal 220vac

Voltage - 100-300vac

Power Factor - > 0.95

Operating Frequency - 230KHz (no flicker)

Operating Temperature range - -25degC to +50degC

Maximum Operating Temperature - +85degC

Certification - SAA approval no. ND140034 , IEC55015 & AS/NZS61347 compliance reports.

Colour Temperature - 3000-6500 Kelvin (5000K is stock item, other colours to order)

Colour Render Index - >85Ra

P/S ratio (Visually Effective Lumen) - 1.96 Lumens per Watt * - 82

Lumen Maintenance - @ 2,000hrs => 95% , @16,000hrs=> 90% , @60,000hrs => 80%

Dimensions - 150W = 275mm diameter x 54mm high , 300W = 391mm diameter x 58mm high

Switching - Instant switching

Life span / Warranty - 80,000 hours average / 2 year lamp and ballast parts warranty

* Subject to 3% variation up or down per fitting

2015 Pricing	
Item	Price
EDL-150W/R (E40)	\$169.00 +GST
EDL-200W/R (E40)	\$179.00 +GST
EDL-250W/R (E40)	\$189.00 +GST
EDL-300W/R (E40)	\$204.00 +GST



Item No.	Power(W)	Lumen(lm)	Visual Effective Lumens (VEL)
UVL150	150W	12,300	24,100
UVL200	200W	16,400	32,150
UVL250	250W	20,500	40,180
UVL300	300W	24,600	48,215